

HITCHCOCK'S MOTORCYCLES LTD OLDWICH LANE WEST CHADWICK END SOLIHULL B93 OEY ENGLAND

E-MAIL info@hitchcocksmotorcycles.com

WEB www.hitchcocksmotorcycles.com

TELEPHONE 01564 783 192

Large rear carrier fitting guide, part number: 92849

1. Identify the four bolts securing the grab rail to the framework under the seat, and remove this from the bike. Place the rear rack in position and using the 4 existing bolts position rack in place.



2. Take the support bars and identify the correct orientation and sides.



3. Mount the lower end of the support bar to the outside of the silencer mounting using the existing fixings as shown below. Do not fully tighten the fixing at this stage.




4. Then, mount the top of the support bar to the inside fixing on the rack using the shorter M6 bolts supplied, as shown below. it may be necessary for a "tweak" of the support bar to line up at this stage.



5. At this stage now check all the fixings are secure. If you are fitting our side pannier frames (92848A) in addition to this large rack, you will need to utilise the additional brackets and fixings as shown below.



6. If you already have the side frames fitted, discard the lower mounting brackets and replace with the new brackets from this kit, as shown below.



7. The orientation of this bracket can be seen fitted below.



8. As a final check, ensure all fixings are tight. Under no circumstances should the rear carrier be used without the support bars fitted.